

Single Phase Standard PDU

Engineered and Designed for Critical Power Distribution

Methode PDUs are engineered to meet the critical power distribution and protection requirements of today's modern data-center racks and cabinets. The ruggedized design is optimized for extreme reliability in harsh environments, ensuring a long-lasting and trouble-free field service life. Utilizing only quality components and robust Methode manufacturing processes, these products deliver the performance needed to meet your efficiency, uptime, durability, and value goals.

Methode Standard PDUs provide a minimal feature set to meet your most basic power infrastructure needs, including both power distribution and branch circuit protection.

Methode Part Number	Form Factor	Input Voltage	Phases	Current Rating	Max Power Capacity	Input Plug	(Qty) Outlets
PDU-121112F10-ME	0RU	208 VAC	1	30A (24A UL)	6.2kW	NEMA L6-30P	(12) C13



Close-up View

Product Features Include:

- High power-receptacle density in a 1/2-length form factor
- Hardwired power input cord, 10ft length. Terminated with NEMA L6-30 plug
- Branch circuit protection, resettable, and fully compliant to UL 60950-1
- Durable 1.2mm cold-rolled steel enclosure
- Mounts vertically (0RU) in standard racks and cabinets. Button and bracket mounting options available, and included with shipment
- Maximum operating temperature of 60°C / 140°F to ensure reliable performance in the most demanding heat-saturated environments

About Product Testing


Methode PDUs undergo rigorous system testing based on 60+ years of expertise in the industry to ensure they meet the quality, performance, and reliability objectives set forth in their design. Independent testing is conducted by third-party laboratories to certify full compliance to international safety, performance, interoperability, and environmental regulations.


Methodé Part Number: PDU-121112F10-ME

TECHNICAL SPECIFICATIONS

MECHANICAL	
• Form Factor	0RU, vertical mount
• Vertical Mounting	Button & bracket mounting options
• Case Construction	1.2mm CRS, black powder coat
• Case Dimensions LxWxD	26.82 x 1.72 x 3.24 in. (681.3 x 43.7 x 82.4 mm)
• Weight (approx.)	8 lbs (3.6kg)
• Power Inlet Cord	10 feet (3.05m), Black

ENVIRONMENTAL	
• Operating Temperature	0°C to +60°C (32°F to 140°F)
• Non-Operating Temp (Storage)	-20°C to 70°C (-4°F to 158°F)
• Humidity Operating/Storage	5% to 90% RH, non-condensing

ELECTRICAL INPUT	
• Power Inlet Connector	Plug: NEMA L6-30P, 2W+GND, Black 
• Nominal Input Voltage Rating	208 VAC, 1-Phase, 60Hz
• Maximum Input Current Rating	30A (24A UL)
• Ingress Protection Level	IP20
• Maximum Power Capacity	6.2kW (5kW UL)

ELECTRICAL OUTPUT	
• (Quantity) Branch Circuit Protection	(2) Resettable 2-pole magnetic circuit breakers, rated 16A, UL489
• Nominal Output Voltage	208 VAC
• (Quantity) Outlet Receptacles	(12) IEC 60320 C13, rated 10A each 

CERTIFICATION/AGENCY APPROVALS/ OTHER	
• EMC Verification	FCC Part 15 Class A
• Safety Certifications	UL, cUL, File No. E343444; CE
• Environmental	RoHS-1, RoHS-2, no exemptions
• Country of Origin/ Manufacture	China
• Warranty	2-Year Limited Product Warranty; Extended warranty available

Methodé PDUs are in stock and available for immediate delivery. We offer a complete portfolio of both Standard and Intelligent PDUs, as well as a variety of power cords to meet your specifications and needs.

Customer support and warranty information is available at www.methode.com/data. **Call your friendly Methodé sales associate for more information today.**

